# 2005 Nissan 350Z Specifications

Specifications are based on latest product information available at the time of printing

#### Mechanical

Engine	
Name	VQ35DE
Cam design	DOHC
Orientation	Longitudinal
Cylinders / configuration	V6 w/ CVTCS & Molybdenum and coated
	pistons
Block / head composition	Aluminum/ aluminum
Displacement	3.5L
Horsepower	287 @ 6,200 rpm
	300 @ 6,400 rpm (35 <sup>th</sup> Anniversary and
	Track Model)
Torque (lb-ft)	274 @ 4,800 rpm
	260 @ 4,800 rpm (35 <sup>th</sup> Anniversary and
	Track Model)
Bore & stroke (mm)	95.5 & 81.4
Compression ratio (:1)	10.3
Maximum engine speed	6,600 rpm
Induction system	Sequential multi-point electronic fuel
	injection
Valvetrain	4 valves per cylinder
Engine mounts	2 liquid: 1 rubber
Recommended fuel	Premium unleaded
Emissions system	Closed loop feedback system w/ 3-way
	catalyst
Emissions certification level	LEV2
Exhaust	Dual (single each side)

Electrical	
Ignition system	Electronic, Nissan Direct Ignition System
	(NDIS)
Starter	1.4KW reduction
Alternator	110 Amp.
Battery	12 Volt

Transmission and Drive	System						
Drive configuration		Mid-mounted front-engine / rear-wheel drive					
Transmission type	6-speed manual	Standard (Base, Entl	h, Perf, Touring 6MT,				
			ick)				
5-speed auto	w/ manual mode	Standard (Touring 5A1	Γ), Optional (Enth, 35 <sup>th</sup>				
		Anr	niv.)				
Gear ratio		<u>M/T</u>	<u>A/T</u>				
1 <sup>st</sup> _		3.794	3.540				
2 <sup>nd</sup>		2.324	2.264				
3 <sup>rd</sup>		1.624	1.471				
4 <sup>th</sup>		1.271	1.000				
5 <sup>th</sup>		1.000	0.834				
6 <sup>th</sup>		0.794	N/A				
Reverse		3.446	2.370				
Final drive ratio		3.538	3.357				
Drive shaft		Carbon Fiber Reinfo	orced Plastic (CFRP)				
Viscous Limited-Slip Differe	ential (VLSD)	Standard on all	models but Base				
Vehicle Dynamic Control (V	DC)	Standard on Perf, To	ouring 6MT and Track				
		mo	dels				
Traction Control System (T	CS)	Standard on all	models but Base				

Brakes	
Standard (standard on all except Track)	
Front Type	Vented disc, single caliper pistons
Rotor size diameter and thickness (in.)	11.65" x 0.95"
Rear Type	Vented disc, single caliper piston
Rotor size diameter and thickness (in.)	11.50" x 0.63"
Brembo® (standard on 35 <sup>th</sup> Anniv/Track)	
Front Type	Vented disc, 4 caliper pistons
Rotor size diameter and thickness (in.)	12.76" x 1.18"
Rear Type	Vented disc, 2 caliper pistons
Rotor size diameter and thickness (in.)	12.68" x 0.87"
Brake Assist (BA)	S
Brake control	Power-assisted (vacuum)
Anti-lock Braking System (ABS)	S
Number of wheels	4
Number of channels	4
Number of sensors	4
Electronic Brake force Distribution (EBD)	S
Parking brake	Hand operated on center console

Steering	
Type	Engine-speed-sensitive power rack-and-
	pinion
Power assisted	S
Overall ratio	15.9
Turns (lock-to-lock)	2.6
Turning diameter (ft.)	35.4
Steering wheel	3-spoke design w/ air bag
Tilt	Manual

Suspension	
Front	Independent multi-link aluminum suspension
Front strut tower bar	S
Stabilizer bar	S
Rear	Independent multi-link aluminum suspension
Integrated strut brace	S
Stabilizer bar	S

Body / Chassis	
Туре	Unibody
Materials (primary)	Corrosion-resistant and high-strength steel
Hood	Aluminum
Rear hatch	Steel

### Exterior

Wheels & Tires	Base	Enth	Perf	Tour 5AT	Tour 6MT	Track	35 <sup>th</sup>
Wheels						-	
Aluminum-alloy (7-spoke) FR: 17"x7.5" RR: 17"x8"	S	S	-	S	ı		
Aluminum-alloy (6-spoke) FR 18"x 8" RR: 18"x8"		-	S	-	S	-	S
Forged Super light aluminum- alloy (6-spoke) FR: 18"x8" RR: 18"x8.5"			-			S	-
Tires							
Bridgestone summer tires – Front 225/50R17 94W, Rear 235/50R17 96W	S	S	-	S		-	
Summer tires - Front 225/45R18 91W, Rear 245/45R18 96W		-	S	ı	S	S	5
Spare tire Temporary (steel) Non-Brembo equipped models: T145/90D16+16x4T			S			-	
Temporary (steel) Brembo Equipped models: T145/80D17+17x4T	- S					5	
Location				Trunk			

Lights	Base	Enth	Perf	Tour 5AT	Tour 6MT	Track	35 <sup>th</sup>
Headlights							
Halogen headlamps	S				-		
Low: xenon HID, Hi: Halogen	-				S		

## Interior

				5AT	6MT		
Capacity		2-seater					
Sport seat cloth	S	S	S	-	-	S	-
Leather		-		S	S	-	S
Type				Bucket			
Heated seats		-		S	S	-	S
Driver seat 8-way manual	S	S	S	-	-	S	-
8-way (4 power, 4 manual)	-	-	-	S	S	-	S
Passenger seat 4-way manual	S	S	S	-	-	S	-
4-way (2 power, 2 manual)	-	-	-	S	S	-	S
Passenger seat back fold down	S						
function							
Seat back pocket (passenger seat)				S			

Audio	Base	Enth	Perf	Tour 5AT	Tour 6MT	Track	35 <sup>th</sup>
Head unit and speakers							
160W AM/FM/CD w/ 6 speakers (w/ digital clock)	S	S	S	-	-	S	
240W Bose® audio with cassette/6CD in-dash/AM/FM/CD changer control (w/ digital clock)	-	-	-	S	S	-	S
Radio Data System (RDS), Bose only	-	-	-	S	S	-	S
Bose AudioPilot™ noise- compensation, Bose only	-	-	-	S	S	-	S
DVD navigation system	-	-	-	0	0	-	S

Instrumentation	
Meters/Gauges	S
Speedometer	
Tachometer	
Coolant temperature	
Fuel level	
LCD dual trip odometer	
3-bay gauges	S
Trip computer	
Tire pressure monitor	
Oil pressure gauge	
Voltmeter	
Indicators	
Clock	S
M/T shift up timing indicator (light)	When equipped with 6MT
A/T indicator	When equipped with 5AT
Cruise Control	N/A with Base model
TCS off	Enth, Tour 5AT
VDC off	Perf, Track, Tour 6MT, 35 <sup>th</sup> Anniv.

Convenience Features	
Cruise control (ASCD)	S (except Base)
Power windows – driver and passenger one-	
touch up/down	S
Power door locks	S
Remote keyless entry system	S
Cupholders – 3 in the front	S
12-volt outlets – 2	S
Passenger assist grip	S
Sunvisors w/ vanity mirrors and lamps	S
2 rear upper storage boxes (1 with navi)	S
Lockable sub-trunk behind passenger seat	S
Inside rear view mirror – auto-dimming	S (N/A on Base model)
HomeLink® Universal Transceiver (UGDO)	S (N/A on Base model)

Safety and Security

Passenger Restraint Systems	
Air bags (SRS)	
Driver (dual-stage with seat belt sensors)	S
Passenger (dual-stage with seat belt	S
sensor)	
SRS side & curtain air bags,	
driver/passenger	0
Outboard seat belts, front	3-point (ALR/ELR for passenger, ELR for
	driver)
Seatbelts with pretensioners and load	
limiters	S
Tether anchorage	S
Power window lockout button	S

Passive Safety	
Zone Body Construction with front and rear	S
crushable zones	
Energy-absorbing steering column	
Hood buckling creases and safety stops	
Body side reinforcements	
Shift interlock system AT	
Clutch interlock system MT	

Security	
Steering wheel locks when key is removed	S
Vehicle Security System	
Immobilizer	

### **Dimensions**

Exterior (inches)	
Wheelbase	104.3
Overall length	169.4
Overall width	71.5
Overall height	51.9
Coefficient of drag (Cd) (front)	0.30 (0.29 Track model)

Interior (inches)	
Head room	38.2
Leg room	42.6
Hip room	53.2
Shoulder room	53.6
Cargo volume	
SAE rating	6.8 cubic feet

Weights	Base	Enth	Perf	Tour 5AT	Tour 6MT	Track	35 <sup>th</sup>
Curb (pounds) M	T 3,213	3,221	3,241	-	3,268	3,251	3,229
A	Т -	3,229	-	3,257	-		3,291
Weight distribution (%) Front/Rea	r			53/47			
GVWR				3,816			

Volume (cubic feet)	
Passenger compartment	50.5
Cargo	6.8
Total	57.3

EPA Fuel Economy (Actual mileage may vary)		
City	MT/AT	20/19
Highway	MT/AT	26/26
Classification		Two Seaters

Options	
DVD-Based Navigation System	Available on Touring 5A/T, Touring 6M/T,
	35 <sup>th</sup> Anniversary models
Side and Curtain Air Bags	Available on all models